

STAGE LIGHTING COMPANY







The most modern shop facilities in the trade -- air conditioned, one level, heavy floor loading capacities, proper illumination, permanent assembly areas, etc.

OVER FIFTY YEARS SERVICE TO THE ENTIRE ENTERTAINMENT INDUSTRY

We Sell and Rent Theatrical Lighting Equipment

This is our latest catalog showing the newest items of stage lighting equipment for the home, church, theatre, television studio, and other locations.

YOUR INQUIRIES FOR FURTHER INFORMATION

ARE INVITED.

Foreword

Our record of service to the entertainment industry of over 50 years qualifies us to present to you our latest catalog of modern stage lighting equipment for the theatre, auditorium, coliseum, TV studio, night club, church, and home.

Orders

All orders must be in writing and accepted only when acknowledged by us. Please order by catalog description and number to avoid errors.

Prices

Prices as listed in this catalog are subject to change without notice. Advances in wages and materials from time to time make this provision necessary. We will advance our prices only when necessity compels us to do so. Lamps are not included in any prices on equipment unless so stated.

Shipment

We will ship by parcel post, express or freight as per your instructions. If given no shipping instructions, we will use our best judgement in selecting carrier. Consignees must hold carrier responsible for losses, damages, and delays in shipment. Our responsibility ends upon receipt of the goods in good condition by the carrier.

Terms

Terms are net cash, no cash discount allowable. To parties of established credit terms are 30 days net. On C.O.D. shipments 25% must accompany order, balance on delivery by carrier. Remittances made are to be in the form of Post Office or Express money orders or Dallas draft. We will not be responsible for remittances lost in transit.

Guarantee.

Our equipment is sold under guarantee. Any defects in the equipment due to workmanship or materials will be promptly rectified if equipment is returned prepaid within 10 days for our examination. Claims for labor, replacements, or damages will not be allowed.

Goods Returned

Do not return goods without our written permission to do so. When permission is given, goods returned must be sent prepaid, and a handling charge allowed for.

General

All prices shown in this catalog are F.O.B. our factory and do not include postage or freight charges. Any taxes whether state, federal, or local must be added to net costs. All prices and conditions as herein stated are contingent on fires, storms, strikes, acts of God, and other conditions beyond our control. Little Stage Lighting Company reserves the right to make changes in equipment and specifications to said equipment without incurring obligation to make the same changes on equipment previously sold.

A large selected stock of lighting equipment is kept on hand for rental purposes at contract rates, including portable dimmer boards, effects such as lightning, clouds, fire, smoke, rain, and many items not illustrated in this catalog. Rental charges must be paid for in advance. All transportation charges must be paid for by the customer.


For other terms, conditions, and rental rates, please write stating particulars.

F-10

Designed and engineered to be used with 1000 watt lamp for throws up to 70', and with 1500 watt lamp up to 100'. The recommended unit for churches and schools where a large volume of light is required, and economy is a factor. A very simple unit to operate.



45° Tilt Angle Weight 61 lbs. Length 42" 56"Height



The OPTO features:


- *A double lever optical control system
- *A three lens optical system
- *Six built-in color slides
- *Alzac reflector
- *Caster stand
- *Telescoping Stand
- *Built-in Iris
- *Built-in Shutter
- *Variable magnification lens system
- *Front color frame and holder
- *Lamps at extra cost

The most powerful and versatile follow spotlight on the market.

The F-10 OPTO spotlight is equipped to use either a 1000 watt T-20 mogul pre-focus, or a 1500 watt T-20 mogul pre-focus lamp.

> F-10R OPTO with caster base (as illustrated) F-10S OPTO with round base

F-6 Strong Super Trouper




Designed for very large theatre and coliseum use, this spotlight is the most powerful spotlight on the market. The best spot to use for throws over 150'.

- * Built-in color boom for 6 colors
- * Ample ventilation
- * Well balanced for ease of operation
- * Produces sharp, clear image
- * Variable lens system
- * Automatic carbon feed
- * Quiet in operation
- * Draws only 20 amperes from 120 volt outlet 240 volt model also available
- * Special short throw model also available

F-6 Strong Super Trouper — complete as illustrated

F-1 Strong Trouper




Designed for throws of over 100', this is the famous spotlight in so many theatres, clubs, and auditoriums.

- * Built-in color boom for 6 colors
- * Ample ventilation
- * Well balanced for ease of operation
- * Produces sharp, clear image
- * Variable lens system
- * Quiet in operation
- * Draws only 10 amperes from 120 volt outlet

F-1 Strong Trouper — complete as illustrated

ELLIPSOIDAL REFLECTOR SPOTLIGHTS

The ellipsoidal reflector spot is designed to provide efficient illumination to regular or irregular shaped areas. Four built-in framing shutters provide the means of varying the size and shape of the image. Adjustment of the lens system allows sharp or soft edged images to be produced. This type of spotlight is today the most popular unit on the market.




8" 1000-2000 WATT ELLIPSOIDAL REFLECTOR SPOTLIGHT

Designed for throws up to 100'. Usually used from balcony or cove positions.

Equipped with:

- Alzac ellipsoidal reflector
- Built-in 4 way framing shutters
- Mogul bi-post socket, asbestos leads
- 8" x 8" Step lens or 8" x 11" step lens 8" plano convex lenses at \$6.00 additional cost
- Yoke suspension
- Color frame
- Lamps at extra cost

E-20Y With yoke only E-20C With pipe clamp (as illustrated)



8" 500-750 WATT VERY NARROW ANGLE ELLIPSOIDAL SPOTLIGHT

Designed for throws up to 100' with 18° spread. Especially good for balcony and cove use in large theatres instead of larger units requiring more power. Also excellent for side boom use where area is restricted.

Equipped with:

- NEW exclusive "40°" 4 way framing shutters NEW "HI-TENSITY" light output
- NEW exclusive OVER-ALL ventilation
- Single 8" x 11" step lens
- ALZAC reflector
- Medium bi-post lampholder, asbestos leads
- Yoke suspension
- Color frame
- Lamps at extra cost

E8N-Y With yoke only E8N-C With pipe clamp (as illustrated)



E8-Y With yoke only E8-C With pipe clamp (as illustrated)

8" 500-750 WATT NARROW ANGLE ELLIPSOIDAL SPOTLIGHT

Designed for throws up to 60 feet with 22° spread. Especially useful for front lighting from balconys, coves, side of theatre, etc; also for side boom locations in larger theatres.

- NEW exclusive "40" 4 way framing shutters NEW "HI-TENSITY" light output
- NEW Exclusive OVER-ALL ventilation
- Single 8" x 8" step lens
- ALŽAC reflector
- Medium bi-post lampholder, asbestos leads
- Yoke suspension
- Color frame
- Lamps at extra cost


6" 500-750 WATT MEDIUM ANGLE ELLIPSOIDAL SPOTLIGHT

Designed for throws up to 45 feet with 28° spread. Especially useful for front lighting from coves, balconys, and for overhead lighting of podium, side lighting on stage, from overhead battens, or from boom.

Equipped with:

- NEW exclusive "40°" 4 way framing shutters NEW "HIGH-TENSITY" light output
- NEW exclusive OVER-ALL ventilation
- Single 6" x 8" step lens
- ALZAC reflector
- Medium bi-post lampholder, asbestos leads
- Yoke suspension
- Color frame
- Lamps at extra cost

E6-Y With voke only E6-C With pipe clamp (as illustrated)



6" 500-750 WATT WIDE ANGLE ELLIPSOIDAL SPOTLIGHT


Designed for throws up to 28 feet with 50° spread. Especially useful for short to medium throws where a sharp edge pattern of light is needed, i.e, from booms next to prescenium, arena theatres, and for special effects.

Equipped with:

- NEW exclusive "40" 4 way framing shutters NEW "HIGH-TENSITY" light output NEW exclusive OVER-ALL ventilation

- Two 6" x 9" plano-convex lenses ALZAC reflector
- Medium bi-post lampholder, asbestos leads
- Yoke suspension
- Color frame
- Lamps at extra cost

E26-Y With yoke only E26-C With pipe clamp (as illustrated)



E6W-Y With yoke only E6W-C With pipe clamp (as illustrated)

6" 500-750 WATT WIDE ANGLE ELLIPSOIDAL SPOTLIGHT

Designed for throws up to 20 feet with 55° wide spread. Especially useful for arena, small theatre, those small throws inside sets, and also for window display applications.

- NEW exclusive "40°" 4 way framing shutters NEW "HIGH-TENSITY" light output
- NEW exclusive OVER-ALL ventilation
- Two 6" x 8" step lenses
- ALZAC reflector
- Medium bi-post lampholder, asbestos leads
- Yoke suspension -
- Color frame
- Lamps at extra cost

A NEW TYPE OF SPOTLIGHT

"Z - LITE"

These units achieve the same purpose as ellipsoidal spots. Yet the long life of the lamps and the lamps abilities to burn in any position, make these spotlights cheaper to own and operate, and more versatile than the fresnel spotlight units.

These are an entirely new type of spotlight: Efficiency, economy, and versatility are their principal points of design.

ADVANTAGES OF THE Z-LITE:

- 2000-Hour life lamp: Minimizing hourly lamp cost. Internal lamp reflections. Surface of the highest efficiency and renewed with lamp.
- Burning position of lamp: Any position allows spotlight to be focused on any angle without deterioration of lamp.
- Lamp available in 115, 120 and 125 volts service ratings. Accommodates latest or oldest power systems, and allows for variations in color temperature.
- New 40° framing shutter design allows adjusting to more acute angles of image than previously possible.
- Lamp rating and ventilation of spotlight allows unit to be used for commercial lighting purposes under prolonged burning periods without deterioration or loss of lamp.



Z6-Y With yoke only Z6-C With pipe clamp (as illustrated)

6" 500 WATT Z-LITE (PATTERN PROJECTING SPOT)

The latest development in the lighting field—another exclusive from LITTLE STAGE LIGHTING CO. These units are designed to equal ellipsoidal spots in purpose and to operate more economically than any other unit of professional ability. Designed for throws up to 40 feet with a 28° spread. These units are useful for use as front lighting, from balcony, coves, side lighting on stage, as well as overhead lights.

Equipped with:

- NEW exclusive " 40° " 4 way framing shutters NEW exclusive OVER-ALL ventilation
- Single 6" x 8" step lens
- Aluminum reflector
- 500 watt PAR 64 lamp (rated life 2000 hours), asbestos leads
- Yoke suspension
- Color frame

6" 500 WATT Z-LITE (PATTERN PROJECTING SPOT)

The latest development in the lighting field—another exclusive from LITTLE STAGE LIGHTING CO. These units are designed to equal ellipsoidal spots in purpose and to operate more economically than any other unit of professional ability. Designed for throws up to 25 feet and 50° spread, these units are useful for use as front lighting, side lighting on stage as well as overhead lights.


- NEW exclusive "40°" 4 way framing shutters
- NEW exclusive OVER-ALL ventilation
- Two 6" x 9" plano-convex lenses Aluminum reflector
- 500 watt PAR 64 lamp (rated life 2000 hours), asbestos leads
- Yoke suspension
- Color frame



Z26-Y With yoke only Z26-C With pipe clamp (as illustrated)

FRESNEL SPOTLIGHTS

The fresnel spotlight is designed to provide efficient illumination to areas where smooth blending of light from several sources are desired. The image projected by the fresnel spotlight has a soft edge and the focus can be varied from wide to narrow spread. With barn door attachments the image can be transformed into rectangular shapes for further variation.




N8-Y With yoke only N8-C With pipe clamp (as illustrated)

8" 1000-2000 WATT FRESNEL SPOTLIGHT

Designed for throws from 25' up to 65'. Excellent for general area blended lighting or for high intensity soft edge spot lighting where sharpness is not desirable or necessary. Beam spread varies from 15° to 35°.

Equipped with:

- * Double wall and OVER-ALL ventilation
- * Single 8" flat fresnel lens
- Polished aluminum reflector
 Mogul pre-face lampholder, asbestos leads
- * Sliding mount with positive tightening screw for focus
- * Yoke suspension
- * Color frame
- * Lamps at extra cost



N6-Y With yoke only N6-C With pipe clamp (as illustrated)

6" 250-750 WATT FRESNEL SPOTLIGHT

Designed for throws from 10' up to 30'. Excellent for general area blended lighting or for high intensity soft edge lighting where sharpness is not desirable or necessary. Beam spread varies from 12° to 50°.

Equipped with:

- * Double wall and OVER-ALL ventilation
- * Single 6" flat fresnel lens
- * ALZAC reflector
- * Medium pre-focus lampholder, asbestos leads
- * Sliding mount with positive tightening screw for focus
- * Yoke suspension
- * Color frame
- * Lamps at extra cost



Small compact light for confined areas—window displays, small scenes short throw distances up to 12 feet.

- * Single contact bayonet base lampholder
- * Aluminum reflector
- * 3" Fresnel lens
- * Yoke suspension and table base
- * Base cord and convenience plug
 - Color frame
- Lamps at extra cost

N3-TB With Table base (as illustrated)

CONDENSER SPOTLIGHTS

Condenser spotlights are designed for economy as well as a variety of uses. The image projected has a well defined edge and is evenly illuminated. Focusing is easy and the image may be varied for large to small. With barn door attachments the condenser spot may also be used to illuminate rectangular areas.



8" 1000-2000 Watt Condenser Spotlight

Equipped with:

- * Single 8" Plano-Convex lens
- * Mogul screw base lampholder, asbestos leads
- * Easy focusing
- * Yoke Suspension
- * Color frame
- * Double wall ventilation
- * Lamps at extra cost

C-8Y	With yoke only	
C-8C	With pipe clamp	

6" 1000-1500 Watt Condenser Spotlight

Equipped with:

- * Single 6" Plano-Convex lens
- * Mogul screw base lampholder, asbestos leads
- * 'Easy focusing
- * Yoke suspension
- * Color frame
- * Double wall ventilation
- * Lamps at extra cost


C-60Y With yoke only C-60C With pipe clamp




Equipped with:


- * Single 6" Plano-Convex lens
- * Mogul screw base lampholder, asbestos leads
- * Easy focusing
- * Yoke suspension
- * Color frame
- * Double wall ventilation
- * Lamps at no extra cost

C-6Y With yoke only C-6C With pipe clamp





41/2" 250-400 Watt Condenser Spotlight



Designed for throws 8' to 18'. A highly useful spotlight for small theatres, displays, etc.

- * Single 41/2" plano-convex lens or 41/2" fresnel lens
- * Medium screw base lampholder, asbestos leads
- * Easy focusing
- * Yoke suspension
- * Color frame
- * Lamps at extra cost

C4-Y With yoke only C4-C With pipe clamp (as illustrated)

Pin Spot Adapter for 41/2" Condenser Spotlight

An auxiliary device providing means to get very sharp, round images. Useful in small clubs.

- * Mounting frame to fit into 41/2" spot
- * 3 Templates with round holes

C4-PA Pin Spot Adapter



11/2" 100-150 Watt Condenser Spotlight

Designed for throws 5' to 15'. One of the most popular items on the market for small clubs. Useful for lighting individual musicians, statues, etc.

- * 11/3" Step lens
- * Single contact bayonet base
- * Easy focusing
- * Yoke suspension
- * Color frame
- * Lamps at extra cost

C-1TB With table base



L22 500-1000 Watt Olivette


The standard for many years of entrance lighting, etc.

- * Heat resisting aluminum finish reflector
- * Universal fitting to fit stand
- * Mogul screw lampholder socket, asbestos leads
- * Color frame at extra cost
- * Lamps at extra cost

L22 Flood light head only

L22-S With 4' stand

L22-R With 4' roller stand



L20 750-1500 Watt Scoop

A newer type of floodlight widely used in TV and motion picture studios. Excellent for cyc lighting in large auditoriums, etc.

- * Matte finish aluminum reflector
- * Mogul screw lampholder with asbestos leads
- * Yoke suspension
- * Color frame at extra cost
- * Lamps at extra cost

L20-Y With yoke only L20-C With pipe clamp




L10 300-500 Watt Scoop

The modern floodlight for most floodlighting applications on the stage. Efficiency, weight saving, and universal usage are the design factors in this unit. Useful for entrance lighting, cyc lighting, area lighting, etc.

- * Matte surface aluminum reflector
- * Mogul screw lampholder with asbestos leads
- * Yoke suspension
- * Color frame and holder
- * Lamps at extra cost


L10-Y With yoke only L10-C With pipe clamp




Efficiency and limited size are principal points of design on this unit. Useful for small entrances, small areas, small backings, etc.

- * Matte surface aluminum reflector
- * Medium screw lampholder with asbestos leads
- * Combination mounting attachment
- * Color frame and holder
- * Lamps at extra cost

L5 Scoop (as illustrated)



R-40 Striplight



B-16-H

- *Wired in three colors on 6" centers
- *Accommodates R-40, or PAR-38 lamps
- *Combination frames with roundels furnished at extra cost
- *Gelatine color frames furnished as standard
- *Weight, per foot 6 lb. approximate
- 6 foot, 12 lite strip with hangers as illustrated B-16-H
- 7-1/2 foot, 15 lite strip with hangers B-18-H
- B-16-R 6 foot, 12 lite strip with rollers
- B-18-R 7-1/2 foot, 15 lite strip with rollers

R-40 Striplight



B-36-R

- *Wired in three colors on 8" centers
- *Accommodates R-40, or PAR-38 lamps
- *Combination frames with roundels furnished at extra cost
- *Gelatine color frames furnished as standard
- *Weight, per foot 6 lb. approximate
- B-36-H 6 foot, 9 lite strip with hangers
- B-38-H 8 foot, 12 lite strip with hangers
- B-36-R 6 foot, 9 lite strip with rollers - as illustrated
- B-38-R 8 foot, 12 lite strip with rollers


Portable Footlights



- *Wired in three colors on 6" centers
- *Angled for proper lighting
- *Each compartment accomodates two lamps
- *Gelatine color frames furnished
- *Weight, per foot 5 lbs. approximate

B-26 6 foot, 12 lite striplight


1000-1500 Watt Linnebach Lantern




Designed on the principal of the shadow box, these units utilize a concentrated filiment light source to project through a painted slide or cutout 24" x 24" and cast a slightly diffused image. Very useful for projecting against backdrops from front or rear.

- * Pedestal legs
- * Flat black finish inside
- * Mogul prefocus lampholder, asbestos leads
- * 24" x 24" Slides at extra cost
- * Lamps at extra cost

LB10 As illustrated






A modern unit for medium distance floodlighting. Very useful for back lighting as sun light or moon light at distances 25'-70'.

- * Ventilation with baffles
- * Alzac reflector
- * Medium prefocus lampholder and asbestos leads
- * Rear focusing handle
- * Yoke suspension
- * Color frame
- * Lamps at extra cost

S-10Y With yoke only S-10C With pipe clamp



R-40 Color Filter Adapter

Designed for economy useage in very small theatres, stages, and also for display work. These attachments allow for gelatine use over R-40 lamps.

- * Ample ventilation for gelatine useage
- * Spring clips for easy fitting on to R-40 lamps
- * Color frame
- * Barn door, snoots and gator clamp extra as illustrated
- * Lamps at extra cost

R-40 Automatic Color Wheel Spot



- *Completely automatic
- *Uses ordinary R-40 lamp
- *Equipped as shown-complete
- *Lamps at extra cost

R-40CW R-40 Automatic Color Wheel Spot

Music Stands



- *Heavy construction for sturdiness
- *Built-in light
- *Portable easily assembled
- *Telescoping stand

MS-1 Music Stand


MS-2 Leaders stand

Shower Lights



Mirror Glass Reflecting Surface
Dance Floor Illumination Tiny Circles
A.C. 110 Volt 60 cycle Motor
Easy to install to any convenient outlet

SH-1	18 inch diameter
SH-2	24 inch diameter
SH-3	30 inch diameter




Color Wheels

CW-1 5 Hole color wheel for 4-1/2" lens spot

CW-2 6 Hole color wheel for 6" lens spot


CW-4 CW-1 with motor (A.C.) 4-1/2" lens

CW-5 CW-2 with motor (A.C.) 6" lens




Barn Doors

	Darii Doorb		
Item No.	Size	Type	For Use In
BD-1	$3-1/2 \times 3-1/2$	4 way	N-3
BD-2	$6-1/2 \times 6-1/2$	2 way	N-6
BD-3	$6-1/2 \times 6-1/2$	4 way	N-6
BD-4	$7-1/2 \times 7-1/2$	2 way	
BD-5	$7-1/2 \times 7-1/2$	4 way	
BD-6	10 x 10	2 way	N- 8
BD-7	10×10	4 way	N-8
BD-8	12 x 12	2 way	N-10
BD-9	12 x 12	4 way	N-10
BD-10	14 x 14	2 way	
BD-11	14 x 14	4 way	
BD-12	16 x 16	2 way	
BD-13	16 x 16	4 way	
BD-14	18 x 18	2 way	
BD-15	18 x 18	4 way	
BD-16		2 way	L-20



Snoots

SN-3	For 3" lens opening
SN-4	For 4-1/2" lens opening
SN-6	For 6" lens opening
SN-8	For 8" lens opening
SN-10	For 10" lens opening
SN-12	for 12" lens opening
When or	dering snoots please specify
color fra	me size with item number as
listed ab	ove.



Connectors

CN-4	15 amp.	asbestos-asbestos
CN-5	15 amp.	asbestos-cable
CN-6	15 amp.	cable-cable
CN-7	30 amp.	asbestos-asbestos
CN-8	30 amp.	asbestos-cable
CN-9	30 amp.	cable-cable
CN-10	15 amp.	3 way branchoff








Stage Plugs

SP-50 50 Amp.	stage	plug
---------------	-------	------







Plugging Boxes

Heavy Steel Construction
Plugs not included in price
Fused Protection - 2 wire service
For 3 Wire Service-Slightly Higher

PB-1	2 outlet
PB-2	3 outlet
PB-3	4 outlet
PB-4	5 outlet
PB-5	6 outlet
PB-6	8 outlet



Lamps for the complete line of spotlights and floodlights shown in this catalog are listed below. For your convenience we have listed lamps as used in the professional theatre and also show which units each lamp is used in. Also we have shown those lamps that are rated for long life. When ordering lamps please order by item number.

тапро р	ioabo or dei	by Rem mumber	•	
		Lamps		
Item	Watts	Base	Life(Hours)	For Use In
100G16 1/2/29S.C.	100	S.C. Bay	200	N-3
100G16 1/2/29D.C.	100	D.C. Bay	200	
250T12/7	250	Med.Pref.	200	•
250T20/47	250	Med.Pref.	200	N-6, S-10
250G/SP	250	Med.	200	C-4, L-5
250G/PSP	250	Med.Pref.	200	N-6
$250\mathrm{G/FL}$	250	Med.	800	C-4, L-5
$250 \mathrm{G/PFL}$	250	Med. Pref.	800	N-6
300PAR56/FL	300	End Prong	2000	
300PAR $56/$ SP	300	End Prong	2000	
400G/SP	400	Med.	200	C-4 L-5
400G/PSP	400	Med. Pref.	200	N-6
$400\mathrm{G/FL}$	400	Med.	800	C-4, L-5
$400 \mathrm{G/PFL}$	400	Med.Pref.	800	N-6
500T12/9	500	Med.Pref.	200	
500T12/8	500	Med.Pref.	800	
500T20/64	500	Med.Pref	500	N-6,S-10
500T14/8	500	Med.Bip.	200	E-6, E-26, E-8, E-8N, E-6W
500T14/7	500	Med.Bip.	800	E-6, E-26, E-8, E-8N, E-6W
500G/SP	500	Mog.	200	C-6
500 PAR 64/NSP	500	Med. Connector	2000	Z-6, Z-26
500G/FL	500	Mog.	800	C-6
750T12/9	750	Med.Pref.	200	
750T14	750	Med. Bip.	200	E-6, E-26, E-8, E-8N, E-6W
750T20	750	Med.Pref.	500	N-6,S-10
LM/T24/5	1000	Mog.Bip.	200	E-20
LM/G40SP4-1/4	1000	Mog.	200	C-6
1MG40SP5-1/4	1000	Mog.	200	C-8, C-60
1M/G40FL	1000	Mog.	800	C-8, C-60
1MT20	1000	Mog. Pref.	50	F10, LB10
1M/G40PSP	1000	Mog. Pref.	200	N-8
1000PS52	1000	Mog.	1000	
1500PS52	1500	-	1000	L-22, L-20
1500F332 1500T24/6	1500	Mog. Pip	200	L-22, L-20
1500124/0 1500G40/15	1500	Mog. Bip.		E-20
1500G40/10	1500	Mog. Pref.	200	N-8
1500G48/6	1500	Mog.	200	C-8, C-60
1500T20/39	1500	Mog.	800	C-8, C-60
2M/T30/1		Mog. Pref.	25	F10, LB10
	2000	Mog. Bip.	200	E-20
2M/G48/17	2000	Mog. Bip.	200	
2M/G48/2	2000	Mog.	200	C-8, C-60
2M/G48/4	2000	Mog. Pref.	200	N-8
				5 minutes on - 10 minutes off.
250A21/60	250	\mathbf{Med}_{ullet}	10	C-4, L-5

GELATINE

Standard Size 20''x24'' Sheet, Sample Gelatine Books Available Minimum Order — 10 Sheets Allow for Postage or Freight When Remitting for Order Please Order by Number and Name

		•			
New	Old	Color	New	Old	Color
No.	No.	. ,	No.	No.	•
		T3t.	0.40	or.	V: alat
201	1	Frost	240	$\frac{25}{190}$	Violet Special Lavender (Surprise Pink)
202	$\frac{71}{70}$	Bastard Amber	242	120	
203	72	Dark Bastard Amber	243	122	Medium Lavender
204	70	No Color Straw	244	26	Dark Lavender
205	2	Light Straw	245	27	Light Purple
206	3	Medium Lemon	246	28M	Medium Purple
207	4	Dark Lemon	247	28	Dark Purple
208		Medium Straw	248	123	Royal Purple
209	6	Straw	250	140	No Color Blue
210	7	No Color Amber	251	29	Daylight Blue
211		Flame	252	_	Pale Blue
212	8	Pale Amber	253	_	Light Sky Blue
$\overline{213}$	9	Light Amber	254	130	Special Steel Blue
$2\overline{14}$	10	Medium Amber	255	30	Azure Blue
$\overline{215}$	11	Golden Amber	$\overline{256}$	$1\overline{2}9$	Light Blue
$\frac{216}{216}$	12	Amber	257	31	Medium Blue
$\frac{210}{217}$	13	Dark Amber	258	$1\overline{3}1$	Light Green Blue
218	109	Orange	$\frac{259}{259}$	32	Green Blue (Moonlight)
$\frac{210}{219}$	$\frac{103}{14}$	Orange-Amber	$\frac{260}{260}$	132	Sky Blue
$\frac{219}{220}$		Pink Red	$\frac{260}{262}$	33	Medium Blue
220			263	33 135	Medium Blue
221	15	Light Red	$\begin{array}{c} 265 \\ 264 \end{array}$	35	Urban Blue
222	110	Fire Red			
223	16	Medium Red	265	138	Dark Blue
224	17	Pure Red	266	37	Dark Urban Blue
225	60	No Color Pink	267	38	Dark Blue
226	112	Flesh Pink	270		Pale Green
227	_	Light Shubert Pink	271	127	Light Green
228	18	Shubert Pink	272	39	Medium Green
229	113	Medium Pink	273	128	Medium Green
230	114	Medium Pink-DuBarry	274	40	Dark Green
231	19	Deep Pink	275		Light Blue Green
232	20	Rose Pink	276	41	Blue Green
233	_	Dark Rose Pink	277	42	Medium Blue Green
236	21	Light Magenta	278	43	Yellow Green
237	$\overline{22}$	Medium Magenta	280	80	Grey
238	$\frac{1}{23}$	Dark Magenta	281	81	Chocolate
$\frac{239}{239}$	$\frac{24}{24}$	Rose Purple	$\frac{1}{282}$	82	Special Chocolate
		was was by			To

PLASTIC GELATINE SHEETS

Size — 20" x 24" Moisture Proof

Suitable for Outdoor Use

Old No.	New	Color	Old No.	New No.	Color
801	No. 9/1	Frost	835	9/116	Medium Salmon Pink
802	9/71	Bastard Amber	837	9/22	Medium Magenta
804	9/70	No Color Straw	838	9/23	Dark Magenta
805	9/2	Light Straw	839	9/24	Rose Purple
806	9/3	Medium Lemon	841	9/117	Surprise Pink
807	9/4	Dark Lemon	842	9/120	Special Lavender
809	9/6	Straw	843	9/118	Medium Lavender
810	9/7	No Color Amber	846	9/28M	Medium Purple
811	9/62	Flame	850	9/140	No Color Blue
813	9/9	Light Amber	851	9/29	Daylite_Blue
815	9/11	Golden Amber	855	9/30	Azure Blue
817	9/13	Dark Amber	856	9/129	Light Blue
818	9/109	Orange	857	9/31	Medium Blue
819	9/14	Orange-Amber	858	9/131	Light Green Blue
821	9/15	Light Red	859	9/32	Green Blue (Moonlight)
823	9/16	Medium Red	861	9/34	Surprise Blue
825	9/60	No Color Pink	863	9/135	Medium Blue
826	9/112	Flesh Pink	866	9/37	Dark Urban Blue
828	9/18	Follies Pink	871	9/127	Light Green
830	9/114	Medium Pink	874	9/40	Medium Green
832	9/20	Rose Pink	877	9/42	Medium Blue Green
834	9/115	Salmon Pink	878	9/43	Yellow Green

Plano Convex Lenses

Plano convex lenses are used in condenser spots, and sometimes in ellipsoidal spots.

T 1.7 (1
Focal Length
6-1/2"
7-1/2"
9"
9"
10"
12"
14"
18"
10"
12"
14"
18"

Step Lenses

Step lenses are used in ellipsoidal spots. These lenses are very efficient, heat resisting, and are today the most popular lenses used in ellipsoidal spots. They produce a defined image without a fine sharp edge, chromatic aberration, or spherical aberration.

Diameter	Focal Length
6"	8"
8"	8"
8"	19″

Fresnel Lenses

Fresnel lenses are used in fresnel type spots and sometimes are used as replacements in condenser spots. They produce a very efficient output of light with a good diffused light that is proper for blending.

Diameter
3"
4-1/2"
6"
8"
10"
12"
14"
16"

Rubber Cable

Type S cord is flexible, heavy duty rubber covered portable cord, that is approved for stage usage, and is suitable for outdoor usage.

Size	Current Carrying
	Capacity
#18/2 Conductor	3 Amperes
#16/2 Conductor	8 Amperes
#14/2 Conductor	15 Amperes
#12/2 Conductor	20 Amperes
#10/2 Conductor	25 Amperes
#8/2 Conductor	35 Amperes
#6/2 Conductor	45 Amperes
#4/2 Conductor	60 Amperes
#2/2 Conductor	80 Amperes

Stage Cable

Type K cord is flexible, fabric covered, heavy duty, portable cord that is approved for stage usage. This cord is also approved under safety codes besides fire and electrical codes.

Size	Current Carrying
•	Capacity
#14/2 Conductor	15 Amperes
#12/2 Conductor	20 Amperes
#10/2 Conductor	25 Amperes
#8/2 Conductor	35 Amperes
#6/2 Conductor	45 Amperes
#4/2 Conductor	60 Amperes
#2/2 Conductor	80 Amperes

Asbestos Wire (extra flexible)

Asbestos type AA cord is used for wiring into all stage lighting equipment and is designed to be durable up to 600° Fahrenheit.

Size	Current Carrying Capacity
#16/1 Conductor	10 Amperes
#14/1 Conductor	30 Amperes
#12/1 Conductor	40 Amperes
#10/1 Conductor	55 Amperes
#8/1 Conductor	70 Amperes
#6/1 Conductor	95 Amperes
#4/1 Conductor	120 Amperes
#2/1 Conductor	165 Amperes


Borderlight Cable

Borderlight cable is available in various sizes. Only #12 conductor is available in compliance with National Electrical Code. Sizes and prices available upon request.


Ward Leonard Modern Lighting Controls

Harry Little Stage Lighting Company makes available Ward Leonards' entire line of modern lighting controls which include: 1- Autotransformer type dimmers, 2-Resistance dimmers, 3-Controlette^R the modern "packaged" lighting control, and 4-Specialized dimming equipment such as motor drives, interlocking dimmers, controls for hot cathode fluorescent lamps, and numerous others.

Most Ward Leonard controls cataloged in these pages are available for immediate shipment from stock. We cordially invite your inquiry on these specialized equipments.




1.2 Kw.VARISTAT Cat.#76-12NH10



2.5 Kw. VARISTAT Cat.#76-43A-NH11



2.5 Kw. VARISTAT Cat. #76-43A-RH11



2.5 VARISTAT Cat.#76-43A-RH10

AUTOTRANSFORMER DIMMERS

Non-Interlocking Type

Ward Leonard Non-Interlocking Lighting Controls are recommended where the simplest form of lamp intensity control is needed. Operated manually from handwheels or slot-closing levers, smooth performing and highly efficient adjustable auto-transformers trade named VARISTAT^(R) and RADIASTAT^(R) supply the controlling device.

Made in four standard sizes, 1.2, 2.5, 6.6 and 8KW to meet practically all applications, non-interlocking units are available in attractive grey finished cabinets for flush or surface mounting as well as open types for inclusion in user's own cabinet. Single or multiple unit assemblies up to three dimmers maximum are listed. FEATURES

- . Smooth, flickerless control
- . VARISTAT or RADIASTAT dimmers
- . 1.2KW to 24 KW
- . Handwheel or slot-closing lever
- . High efficiency . . . low in cost

MOTOR DRIVES - Available for remote, versatile, finger-tip control of VARISTAT and RADIASTAT autotransformer dimmers. Motorlite control system is for simplified, direct switch control; Regulite a servo type for positive remote positioning of intensity. When requesting information, state: number and size of dimmers per drive, traverse time and type of control.

ROUND HANDWHEELS - AUTOTRANSFORMER

		3.f A 37		. "
		MAX.		
		OUTPUT per	NO.	\mathtt{TOTAL}
CATALOG NUMBERS		DIMMER	of	OUTPUT
Enclosed*	Open Type	KW	DIMMERS	KW
76-12RH11	76-12RH10**	1.2	1	1.2
76-43A-RH11	76-43A-RH10**	2.5	1	2.5
76-43A-RH21	76-43A-RH20**	2.5	2	5.0
76-43A-RH31	76-43A-RH30**	2.5	3	7.5
76-37RH11	76-37RH10	6.6	1	6.6
76-37RH21	76-37RH20	6.6	2	13.2
76-37RH31_	76 - 37RH30	6.6	3	19.8
76-38RH11	76-38RH10	8	1	8.0
76 - 38RH21	76 - 38RH20	8	2	16.0
76-38RH31	76-38RH30	. 8	3	24.0

^{*}Enclosure can be furnished in either flush or surface type.


If not specified at time of order, a surface type enclosure will be furnished as standard.

^{**}Where handle extension is required, add Cat. No. 77-62C handle extension " to order.


S	LOT-CLOSING -	AUTOTRA	NSFORMER	
		MAX.		
		OUTPUT per	r NO.	TOTAL
CATALOG 1	NUMBERS	DIMMER	of	OUTPUT
Enclosed*	Open Type	KW	DIMMERS	KW
76-12NH11	76-12NH10	1.2	1	1.2
76-43A-NH11	76-43A-NH10	2.5	1	1.2

^{*}Enclosure can be furnished in either flush or surface type.

If not specified at time or order, a surface type enclosure will be furnished as standard.



6.6 Kw. RADIASTAT Cat. # 76-37RH10



Typical Motor Driven VARISTAT 6-2.5 Kw. VARISTATS


CONTROLETTE

The Modern Packaged Lighting Control


The Famous Ward Leonard "Controlite" dimmer bank is now available in a modern, miniaturized, packaged version. This offers an inexpensive simplified, high performance system ideal for small T-V studios, schools, churches, restaurants, etc., and wherever a large, complex and costly switchboard can be avoided.

CONTROLETTES provide control flexibility in packaged forms in a choice of 3, 4, 5, or 6 individual lighting controllers. Each individual controller can be interlocked mechanically with one another or, where furnished, to a master lever.

Each CONTROLETTE is a complete easy-to-operate dimmer system with built-in circuit protection. Trouble free, silent operating VARISTATS permit smooth accurate control from full bright to blackout.



3-Unit Controlette w/Master Handle Cat. No. 76-43P-4



5-Unit Controlette w/Master Handle Cat. No. 76-43P-28

CONTROLETTE Model Nos. (without master handle)

	No. of			MODEL NU	MBERS	
Total	2500		Туре	of Output	Connection	
Output	Watt	Solid	Duplex	Duplex	Single	Double
Watts	Controllers	Output*	Recpt*	Twist Lock*	Pin Plug*	Pin Plug*
7,500	3	76 - 43P1	76 - 43P3	76 - 43P5	76 - 43P7	76 - 43P9
10,000	4	76 - 43P11	76 - 43P13	76 - 43P15	76 - 43P17	76 - 43P19
12,500	5	76 - 43P21	76 - 43P23	76 - 43P25	76 - 43P27	76 - 43P29
15,000	. 6	76 - 43P31	76 - 43P33	76 - 43P35	76 - 43P37	76-43P39

^{*}Master Lever optional at extra cost

^{*}Number of circuits per controller depends on type of output connection selection. Solid output is per application. Single pin plug provides 4 circuits per controller; all other connections furnish 2 circuits per controller.

resistance dimmers

WARD LEONARD NON-INTERLOCKING RESISTANCE DIMMERS

Our	Min. & Max.	Plate Diameter
${f Number}$	Watts	
71-104	255/400	8 inch
71-105	405/550	8 inch
71-106	555/650	8 inch
71-119	655/750	13 inch
71-107	755/1000	13 inch
71-108	1005/1350	13 inch
71-109	1355/1650	15-1/2 inch
71-110	1655/2000	15-1/2 inch
71-111	2005/2450	18 inch
71-120	2455/2700	18 inch
71-112	2705/3000	18 inch
71-113	3005/3300	2/15-1/2 inch plates
71-114	3305/4000	2/15-1/2 inch plates
71-115	4005/4900	2/18 inch plates
71-116	4905/6000	2/18 inch plates
71-117	6005/7350	3/18 inch plates
71-118	7355/9000	3/18 inch plates
	·	•

For 110/120 volt 2 wire service

INTERLOCKING DIMMERS

For larger, more complex lighting control installations, a full line of interlocking controls utilizing VARISTAT or RADISTAT autotransformer dimmers or VITROHM resistance plates in open or enclosed type frameworks, can be obtained on special order.

SPECIALIZED CONTROLS

Magnetic amplifiers, cycle dimmers, hot and cold cathode lamp dimming represent just a few additional modern lighting controls "result-Engineered" by Ward Leonard. Details on request.

THE COMPACT

"PACKAGED" LIGHTING CONTROLLER


Now, the highly versatile CONTROLETTE "packaged" lighting controller has been further improved to include still more outstanding features. Note the reduced size of the six unit CONTROLETTE pictured. The three and four unit sizes have been made more compact too. In the new design CONTROLETTE each controller is equipped with two circuit breakers; one pole fir input (25 amp.) and one pole for output (20 mp.) protection.

A master control lever is furnished for either right or left hand side.

Now all CONTROLETTES come equipped with a fused (10 amp.) constant circuit receptacle. Panels available are: Solid output, Grounded twist-locks (20 amp.), Duplex grounded twist-lock (15 amp.) and Three-pin grounded stage connector (30 amp.).

Receptacle panels may now be located on the front top or back.

New design CONTROLETTE "packaged" dimmers are available in 3, 4 and 6 unit sizes with total output rated at 7,500, 10,000 and 15,000 watts respectively. The individual VARISTAT circuit controllers are rated at 2,500 watts maximum a ndare equipped with interlocking levers so that each may be interlocked to the master.



Also available for the first time is a 3-unit CONTROLETTE with 19,800 watts total output, 6.6KW per circuit. This unit for higher capacity circuits has same dimensions and features as the 6-unit 15,000 watt CONTROLETTE.

COMPACT CONTROLETTE (with Master Handle)

Catalog Numbers	Total Output Watts	No. and Rating of Controllers	Type of Output Connection	Output Panel Accessory See Schedule	Master Handle Location
76-43P-3R	7,500	3-2.5KW	SOLID OUTPUT	"A"	RH
76-43P-3L	7,500	3-2.5KW	SOLID OUTPUT	"A"	LH
76-43P-4R	10,000	4-2.5KW	SOLID OUTPUT	″B″	RH
76-43P-4L	10,000	4-2.5KW	SOLID OUTPUT	"B"	LH
76-43P-6R	15,000	6-2.5KW	SOLID OUTPUT	"C"	RH
76-43P-6L	15,000	6-2.5KW	SOLID OUTPUT	"C"	LH
76-37P-3R	19,800	3-6.6KW	SOLID OUTPUT	"D"	RH
76-37P-3L	19,800	3-6.6KW	SOLID OUTPUT	"D"	LH

ACCESSORIES FOR CONTROLETTE OUTPUT PANELS

Schedule	Cat. No.	Description *		
"A"	76P-3T-15	GROUNDED TWIST LOCK DUPLEX	3-15 AMP	
"A"	76P-3T-20	GROUNDED TWIST LOCK	3-20 AMP	
"A"	76P-3GP	GROUNDED STAGE PLUG CONNECTOR	6-30 AMP	
"B"	76P-4T-15	GROUNDED TWIST LOCK DUPLEX	4-15 AMP	
"B"	76P-4T-20	GROUNDED TWIST LOCK	4-20 AMP.	
"B"	76P-4GP	GROUNDED STAGE PLUG CONNECTOR	8-30 AMP.	
"C"	76P-6T-15	GROUNDED TWIST LOCK DUPLEX	6-15 AMP.	
"C"	76P-6T-20	GRONDED TWIST LOCK	6-20 AMP.	
"C"	76P-6GP	GROUNDED STAGE PLUG CONNECTOR	12-30 AMP.	
"D"	76P-9T-15	GROUNDED TWIST LOCK DUPLEX	9-15 AMP.	
"D"	76P-9 T -20	GROUNDED TWIST LOCK	9-20 AMP.	
"D"	76P-9GP	GROUNDED STAGE PLUG CONNECTOR	18-30 AMP.	

^{*} These connections furnish 2 circuits per controller.

LITTLE STAGE LIGHTING COMPANY

10507 Harry Hines Blvd.

Dallas 20, Texas

PRICE SCHEDULE

Effective February 16, 1962

Page	Catalog Number	Price	Page Catalog Number	Price
3	F-10R	\$ 250.00	12 В18-н	\$ 122.00
-	F-10S	240.00	12 · · · · · B16-R · · · · · ·	100.00
4	F-6	2350.00	12 · · · · · B18-R · · · · · ·	117.00
4	F-1	1200.00 .	12 · · · · · B36-H · · · · ·	95.00
5	E20-Y	117.00	12 · · · · · B38-H · · · · ·	122.00
5 · · · · 5 · · · ·	E2O-C	120.00	12 · · · · · B36-R · · · · ·	100.00
5	E8N-Y	82.00	12 · · · · · B38-R · · · · · ·	117.00
5	E8N-C	85.00	12 ····· B26 ·····	72.00
5	E8-Y	82.00	13 · · · · LB10 · · · · ·	114.00
5	E8-C	85.00	13 ····· S10-Y ·····	47.00
6	Е6-У	47.00	13 ····· S10-C ·····	50.00
6	E6-C	50.00	13 · · · · RHO_CA · · · · ·	
6	E26-Y	57.00	13 · · · · · R40-BD · · · · ·	3.00
6	E26-C	60.00	13 · · · · · R40-SN · · · · ·	2.50
6	E6W-Y	52.00	13 · · · · · A-14sw · · · · ·	2.50
_	E6W-C	55.00	14 · · · · · R40-CW · · · · ·	5.00
	Z6-Y	47.00	14 · · · · · MS-1	22.50
, –	Z6-C	50.00	14 · · · · · MS-2	22.00
Ź	Z26-Y	57.00		60.00
7 	Z26-C	60.00	14 · · · · · SH-1	120.00
á	N8-Y		14 · · · · · SH-2 · · · · ·	145.00
8	N8-C	47.00	1 ⁴ · · · · SH-3	220.00
8	N6-Y	50.00	1'+ · · · · · CW-1	6.00
8		21.00	14 · · · · · CW-2	8.00
	N6-C	24.00	1 1 CW-1+	30.00
8	N3-TB	15.00	14 · · · · · CW-5	45.00
9	C8-Y	47.00	15 · · · · A-1	6.50
9 •••	C8-C	50.00	15 ····· A-2 ·····	10.00
9 •••	C60-Y	37.00	15 · · · · · A-3 · · · · · ·	25.00
9 •.••	C60-C	40.00	15 · · · · · A-4 · · · · · · · · · · · · · · · · · · ·	15.00
9 • • •	<u>C6-Y</u>	27.00	15 · · · · · A-5 · · · · · · ·	20.00
/	<u>C6-C</u>	30.00	15 · · · · · A-6 · · · · · ·	35.00
0 •••	· · · · · · · · · · · · · · · · · · ·	12.00	15 · · · · · A-7 · · · · · ·	1.00
_	C)+-C	15.00	15 · · · · · A-8 · · · · · ·	1.25
0	•••• C ¹ +-PA •••••	1 ¹ +•00	15 · · · · · A-9 · · · · · ·	7.0ó
	•••• Cl-TB	10.00	15 · · · · · A-10 · · · · · ·	3.00
	L22	25.00	15 · · · · · A-11 · · · · · ·	3.00
	L22-S	45.00	15 ····· A-12 ·····	3.00
	L22-R	60.00	15 ····· A-13 ·····	2.50
	L20-Y	33.00	15 A-14	3.25
1	L20-C	36.60	15 A-15	3.00
	L10-Y	27.00		2.50
	L10-C	30.00		15.00
	L5	16.00		
	В16-н	95.00		18.00
	TOTA DECEMBER 1	//•UU	15 A-19	20.00

Page Catalog Number	Price	Page Catalog Numb	er Price
15		16	\$ 48.00 55.00 60.00 75.00 72.29S.C. 2.10 72.29D.C. 2.70 72.1

Page Catalog Number Pric	ce Page Catalog Number Price	
Plano-Convex Lenses Round Handwheels - Autotransformer		
19 4-1/2" Dia \$ 4.3 19 6" Dia 6.0 19 8" Dia. 16.0	00 21 76-12R11 \$ 56.00	
19 6" Dia. Step 5.5 19 8" x 8" Step 9.0 19 8" x 11" Step 9.0	21. 76-37RH11. 240.00 21. 76-37RH21. 460.00 00 21. 76-37RH31. 680.00 00 21. 76-38RH11. 380.00 21. 76-38RH21. 740.00	
19 3" Dia 1.2 19 4-1/2" Dia 2.0 19 6" Dia 3.0 19 8" Dia 5.0 19 10" Dia 12.0 19 12" Dia 20.0 19 14" Dia 24.0 19 16" Dia 36.0	00 2176-12RH1038.50 00 2176-43A-RH1070.00 00 2176-43A-RH20150.00 00 2176-43A-RH30225.00 00 2176-37RH10160.00	
Rubber Cable	21 76-38RH10 300.00 21 76-38RH20 600.00	
19 18/2 (per ft.) 0.0 19 16/2 (per ft.) 0.0 19 14/2 (per ft.) 0.1 19 12/2 (per ft.) 0.1	06 21 76-38RH30 900.00 08 12 Slot Closing - Autotransformer 18 Enclosed	
19 10/2 (per ft.) 0.2 19 8/2 (per ft.) 0.4 19 6/2 (per ft.) 0.5 19 4/2 (per ft.) 2.2 19 2/2 (per ft.) 3.0	45 21 76-12NH11 72.50 57 21 76-43A-NH11 124.00 25	
Stage Cable	21 76-12NH10 55.00 21 76-43A-NH10 84.00	
19 14/2 (per ft.) 0.1 19 12/2 (per ft.) 0.1 19 10/2 (per ft.) 0.2 19 8/2 (per ft.) 0.4 19 6/2 (per ft.) 0.5 19 4/2 (per ft.) 2.2	18 Controlette 24 (Without Master Handle) 45 3 Unit 57	
19 4/2 (per ft.) 2.2 19 2/2 (per ft.) 3.0		
Asbestos Wire	2276-\(\frac{1}{3}\)P7 665.00 2276-\(\frac{1}{3}\)P9 665.00	
19 16/1 (per ft.) 0.0 19 14/1 (per ft.) 0.1 19 12/1 (per ft.) 0.1 19 10/1 (per ft.) 0.1 19 8/1 (per ft.) 0.2 19 6/1 (per ft.) 0.3 19 4/1 (per ft.) 0.4 19 2/1 (per ft.) 0.5	10	

,

Page Cat	alog Number	Price	Page Catalog Number Price
5 Unit			
22 22 22 22 22 6 Unit	76-43P21 \$ 76-43P23 76-43P25 76-43P27 76-43P29	900.00 940.00 940.00 950.00 950.00	23 71-112 \$ 75.00 23 71-113 108.00 23 71-114 108.00 23 71-115 126.00 23 71-116 126.00 23 71-117 183.00 23 71-118 183.00
22 22 22 22	76-43P31 76-43P33 76-43P35 76-43P37 76-43P39	1000.00 1050.00 1050.00 1070.00	2 ⁴ 76- ⁴ 3P-3R 715.00 2 ⁴ 76- ⁴ 3P-3L 715.00 2 ⁴ 76- ⁴ 3P- ⁴ R 825.00 2 ⁴ 76- ⁴ 3P- ⁴ L 825.00 2 ⁴ 76- ⁴ 3P-6R 1125.00 2 ⁴ 76- ⁴ 3P-6L 1125.00 2 ⁴ 76- ³ 7P-3R 1060.00
<u>PLEASE NO</u> Extra cha: Master Ha	rge with	25.00	24 76-37P-3L 1060.00 24 76P-3T-15 40.00 24 76P-3T-20 40.00
23 23 23 23 23 23 23 23	71-104 71-105 71-106 71-119 71-107 71-108 71-109 71-110 71-111	28.00 28.00 28.00 45.00 45.00 45.00 61.00 67.00 67.00	24 76P-3GP 60.00 24 76P-4T-15 50.00 24 76P-4T-20 50.00 24 76P-4GP 75.00 24 76P-6T-15 70.00 24 76P-6T-20 70.00 24 76P-6GP 100.00 24 76P-9T-15 100.00 24 76P-9T-20 100.00 24 76P-9GP 150.00

ALL PRICES QUOTED F.O.B. DALLAS, TEXAS

Our Catalog 3 illustrates only those items that are standard, ordinary, economically useable items. Therefore, Catalog 3 serves as a suitable guide in selecting equipment for theatrical usage, and achieving the professional touch. Many items are not illustrated in this catalog because they are of a more special nature - either because of special usage, or a limited number of applications. Some of these items include: odd size color frames; roundels; reflector type striplights and borderlights; larger wattage lighting equipment; special globes; and effects such as clouds, fire, rain, snow, and lightning.

Regarding quotations, on equipment and supplies not covered in Catalog 3, please write stating your requirements.

