

LED 4 LASER

Thank you for your purchase of the four Cikuan LED headlights, which is characterized by a hint of smoke only under the effect of!

LED light source: R, G, B 256PCS LED red. Green. Blue three kinds of color change

Self-propelled model

Voice Mode

Standard DMX 512 signal control

Power Supply: AC100V-240V 50/60HZ

Power: 20w

Operating temperature: Indoor 200C-400C

Dimension:

Packing Size:

Net Weight: 3KG Gross Weight: 3.7KG

Installation

1, the lamp can be fixed in any position, but the lighting and the persons or objects can not be close to the distance between the 1-meter, and to ensure a firm inlay is good, and precautionary measures, lamps should be safe ground.

2, to ensure that manufacturers set the voltage and frequency for your local power, properly connect well the lights, you can open the power.

3, DMX512 connections:

DMX512 control signal generator through the lamp "input" and "output" of the 3-pin XLR-seat, (1, the two negative and three positive) has been goes on. (Note: If not controlled, add the signals 2 and 3 feet reversed welding, general control units do not have to swap the two feet. Signal line length should be in the 100 meters, to prevent the signal line is too long, and by other electrical appliances interference.

Instructions

1. Address Code 1 ON, procedures for the self-propelled

2. Address code are all OFF, as the voice

3. Address Code 1,10 to ON, the DMX512 control

Four-Channel Description:

Channel function

10-70 Voice

71-139 Self-propelled

140-255 DMX

21-255 pattern selection

31-255 Channel 2 is 0, the pattern runs

40-255 slow speed by approaching